



FLAT ROOFER'S BRACKET W/ 2 D-RINGS

DISPOSITIVI DI ANCORAGGIO

Protezione anticaduta



Benefici



Compatibilità

- Collegabile all'imbracatura e al portautensili

Campi di utilizzo

- Lavori pubblici
- Edificio
- Finitura / artigiani
- Industria pesante
- Industria leggera
- Petrolio e gas minerario (estrazione)

Certificazioni e norme

ANSI-ASSE Z359.12:2009



CSA Z259.12

Protegge contro i rischi



Caduta



FLAT ROOFER'S BRACKET W/ 2 D-RINGS

DISPOSITIVI DI ANCORAGGIO

Protezione anticaduta

Dettagli - Norme

Dettagli tecnici

Tipo di attrezzatura	Staffa per tetti piani con 2 forature
Composizione del supporto principale	Acciaio inox
Elementi inclusi	Portautensili laterali con anello a D
Colore	Grigio
Dimensione	Taglia unica
Tipo di imballaggio	Scatola da 10
Peso (lbs)	2.20



Fall protection

FLAT ROOFER'S BRACKET W/ 2 D-RINGS

ANCHORAGE DEVICES

Our flat roofer's bracket with double D-rings allows workers to attach their fall protection equipment, such as lanyards or lifelines, securely to the bracket.

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
WCA21300	Grey	30 m	FLAT ROOFER'S BRACKET W/ 2 D-RINGS	776285852130	10776285852135	12	1	0.0 kg	0.0 cm	0.0 cm	0.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height