



FLAT ROOFER'S BRACKET W/ 2 D-RINGS

URZĄDZENIA KOTWICZĄCE

Ochrona przed upadkiem



Zalety



Kompatybilność

• Możliwość podłączenia do szelek i uchwytu na narzędzia

Obszar użytkowania

- Roboty publiczne
- Budownictwo
- Prace remontowe / Rzemiosło
- Przemysł ciężki
- Przemysł lekki
- Ropa i gaz (wydobycie)

Certyfikaty i normy



CSA Z259.12

Chroni przed



Upadek



FLAT ROOFER'S BRACKET W/ 2 D-RINGS

URZĄDZENIA KOTWICZĄCE

Ochrona przed upadkiem

Szczegóły - Normy

Dane techniczne

Rodzaj wyposażenia	Wspornik do dachów płaskich z 2 otworami
Skład głównego wkładu	Stal nierdzewna
W zestawie	Boczne uchwyty na narzędzia typu D-ring
Kolor	Szary
Rozmiary	Jeden rozmiar
Rodzaj opakowania	Pudełko 10
Weight (lbs)	2.20



Fall protection

FLAT ROOFER'S BRACKET W/ 2 D-RINGS

ANCHORAGE DEVICES

Our flat roofer's bracket with double D-rings allows workers to attach their fall protection equipment, such as lanyards or lifelines, securely to the bracket.

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
WCA21300	Grey	30 m	FLAT ROOFER'S BRACKET W/ 2 D-RINGS	776285852130	10776285852135	12	1	0.0 kg	0.0 cm	0.0 cm	0.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height