



坠落防护

PROTECTOR ROUND AN181C15

可伸缩防坠落装置

带提手的自收式防坠落绳，便于运输和安装，适用距离最长可达15米



具体优势



舒适性

- 双旋转挂钩，实现最佳用户跟踪



高性能

- 认证的最大额定负载在100kg以上：产品认证在150kg以下



易用性

- 携带手柄，便于运输
- NFC系统保证可追溯性



耐用性

- 抗冲击ABS外壳



可见性

- 视觉坠落指示器，用于即时验证产品是否正常工作

标准和认证



EN360:2023

150 KG

150 KG (最大额定负载)

50 KG (最小额定负载)

F0 | 使用: 垂直

应用行业

- 重工业
- 轻工业
- 维修业
- 汽车业
- 石油和天然气 (开采)
- 清洁

防范风险



坠落



enjoy safety

编辑 05/08/2026
www.deltaplus.com.cn



坠落防护

PROTECTOR ROUND AN181C15

可伸缩防坠落装置

带提手的自收式防坠落绳，便于运输和安装，适用距离最长可达15米

详细信息 - 标准

技术细节

装备类型	钢缆卷轴
主要支架的组成	ABS, 钢, 不锈钢
最大长度 (m)	15
最小长度 (m)	0,6
ARA长度 (m)	15
ARA长度 (inch)	590.5515
Lock	Automatic system
坠落指数	F0
绳索直径 (mm)	4,5
包含配件	包含能量吸收器
颜色	黑色-橙色
连接器 (用户方)	小钩，钢制，开口21mm
产品优势	坠落指示器
连接器 (结构方)	螺纹钩环，钢制，18mm开口
自生产之日起的产品寿命 (年)	20
重量 (kg)	6.5
一人最大载重量 (kg)	150
包装类型	单独出售
防坠落作业类型	长距离垂直移动或倾斜表面上的移动, 垂直结构上的长距离水平移动
锁定系统	惯性锁定系统
最大额定负载 (kg)	150
Use of self retracting	Vertical



Fall protection

PROTECTOR ROUND AN181C15

RETRACTABLE FALL ARRESTERS

Self-retractable cable fall arrester with carry handle to ease transportation and installation for distances of up to 15 metres

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN181C15	Black-Orange	20 m	PROTECTOR ROUND AN181C15	3295249324247	100000000000007	1	1	7.0 kg	39.0 cm	28.0 cm	14.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height