



Hand protection

VENICUT55

SLIGHTLY SHARP AND LONG-LASTING WORK



Applications

- Public Works
- Building
- Finishing Works/Craftsmanship
- Manufacturing/Transformation
- Accommodation & Food Services
- Maintenance

Certifications and norms



EN 388
3 X 4 X C



EN 407
X 1 X X X X



A3 X X

Risk Protection



Heat



Cutting



Wearing



VENICUT55

SLIGHTLY SHARP AND LONG-LASTING WORK

Hand protection

Standards - Details



EN388:2016+A1:2018

3 [0-4] ABRASION RESISTANCE
X [0-5] CUT RESISTANCE
4 [0-4] TEAR RESISTANCE
X [0-4] PIERCE RESISTANCE
C [A-F] CUT RESISTANCE ISO 13997



EN 407

X [0-4] BURNING BEHAVIOUR
1 [0-4] CONTACT HEAT RESISTANCE
X [0-4] CONVECTIVE HEAT
X [0-4] RADIANT HEAT RESISTANCE
X [0-4] SMALL DROP MOLTEN METAL
X [0-4] LARGE QUANTITY MOLTEN METAL

Technical details

Glove kind	Mechanical glove
Glove family	Knitted coated glove
Mechanical Glove Type	Tricot
Fiber	HEATnocut
Coating Level	Palm Coating
Coating Material	Nitrile
Coating Finish	Smooth
Number of Coatings	Single Coated
Gauge	10
Color	Yellow-Grey
Size	7, 9, 10
Type of conditioning	in individual bag

Packaging

Sale unit: in individual bag
120 pairs /box



Safety gloves

VENICUT55

SLIGHTLY SHARP AND LONG-LASTING WORK

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
VECUT5507	Yellow-Grey	07	VENICUT55	0	0	120	12	10.7 kg	30.4 cm	65.8 cm	28.0 cm
VECUT5509	Yellow-Grey	09	VENICUT55	0	0	120	12	12.0 kg	30.2 cm	66.2 cm	29.6 cm
VECUT5510	Yellow-Grey	10	VENICUT55	0	0	120	12	12.6 kg	30.6 cm	66.4 cm	28.6 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height