



Fall protection

AN547180JWW

ENERGY ABSORBING LANYARDS

Energy absorbing lanyard made of lightweight elastic webbing, providing freedom of movement



Specific benefits



Hygiene

- Can wash harnesses and textiles with neutral soap



Ease of Use

- NFC system guarantees traceability



Sustainability

- High webbing tenacity thanks to its weave and width

Applications

- Public Works
- Building
- Finishing Works/Craftsmanship
- Heavy Industry
- Light Industry
- Maintenance

Certifications and norms

ANSI Z359.13-2013



CSA Z259.11-17

Risk Protection



Fall



Fall protection

AN547180JWW

ENERGY ABSORBING LANYARDS

Energy absorbing lanyard made of lightweight elastic webbing, providing freedom of movement

Standards - Details

Technical details

Type of equipment	Flat webbing lanyard
Composition of the main support	Galvanized steel, Polyester
Max. length (m)	1.8
Max. length (ft)	6
Min. length (m)	1.3
Min. length (ft)	4.3
Length (m)	1,8
Color	Black-Yellow
Connector 1	Small hook, steel, opening 21 mm
Ending	3 sewn thimble loops
Connectors (structure side)	2 automatic lock hook, steel, opening 65 mm
Lifespan from manufacturing (years)	10
Weight (kg)	2.6
Type of conditioning	Box of 5
Fall arrest work situations	Vertical movement on a permanent structure, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection
Lenght (ft)	5.9055



Fall protection

AN547180JWW

ENERGY ABSORBING LANYARDS

Energy absorbing lanyard made of lightweight elastic webbing, providing freedom of movement

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code			Weight			
AN547180JWW	Black-Yellow	1,3 → 1,8 m	AN547180JWW	3295249219475	13295249219472	5	1	13.6 kg	44.0 cm	28.0 cm	22.0 cm



Multiple sales



Minimum sales



Box Width



Box Depth



Box Height